

# OSCAR-15A



## Physical Information:

LF Component	15"(380mm.) Cone Speaker
HF Component	1"(25.4mm.)Diaphragm
Construction	Injection molded High Impact Polycarbonate Color Black
Grille	Powder Coated Steel Mesh
Ringin/Fitting	2x Recessed carrying handle side,top 1x35mm.pole mounting socket 4x Recessed M10 mounting point for flying hardware
Standard Packing	1 Pcs./Pack

Unit Weight	19.8 Kgs.
Gross Weight	22.8 Kgs.
Packing Dimension (HxWxD)	77.5x46.0x50.5

### **General Specifications:**

Type	Two Way Full Range Bass ReFlex Powered Speaker
Sensitivity @ 1W 1M	96 dB
Frequency Response	50Hz-20 kHz
Nominal Dispersion	90 H x 60 V
Dimension (HxWxD)	700.0mm X 445.0mm x 400.0mm. (27.5") x (17.5") x (15.7")
Maximum SPL	122dB

### **Power Amplifier Specifications:**

LF Amplifier	300W Class-D SMPS.
HF Amplifier	50W Class-AB
Input	
Mic	1x Female XLR 1x1/4" Mono
Line	1x Female XLR 1xStereo RCA
Output	1x XLR Male Link Through
Individual Mic, Line, Master Volume Control	
Indicators	Power On/Clip
Power Requirement	230V 50Hz